

# ONCILLA MACHINE VISION COMPUTER

## CoaXPress Frame Grabber System

- Oncilla Industrial PC
- FireBird Quad CXP-12 Frame Grabber
- RISC based ActiveDMA engine technology
- Ruggedized solution for Machine Vision

### FEATURES

---

- 12<sup>th</sup> Gen Intel Alder Lake-S Series Core i7 12700TE Processor.
- 16GB DDR5 SDRAM.
- 256GB SSD Drive.
- FireBird Quad CXP-12 Frame Grabber installed.
- High performance CXP 2.1 with up to 50 Gbps input rate.
- ActiveDMA engine – acquisition with zero CPU usage.
- Comprehensive I/O including end bracket I/O.
- Supports PoCXP (Power over CoaXPress).
- Full GenICam support (including GenTL Producer).
- Proven ActiveCapture & ActiveSDK included.



### OVERVIEW

---

**Oncilla Machine Vision Computer – CoaXPress** is a rugged and compact industrial PC designed specifically for capturing and transmitting high-quality images and video while leaving plenty of compute power for other processing tasks. Incorporating a FireBird Quad CXP-12 Frame Grabber including support for PoCXP and preinstalled operating system plus Active Silicon software and software development kit produces a complete machine vision system.

**Oncilla systems** are designed and thoroughly tested with Active Silicon's latest software and firmware and are part of the continuing regression testing program for new firmware and software releases. The PC hardware has passed multiple international certifications including those for rail and military industries, ensuring stable and reliable performance in diverse harsh environments. The system is designed with longevity in mind using long-term availability components and processor, the same system configuration availability is targeted at a minimum of seven years.

Having a known good platform to build a vision system on can save many hours of system integration, and including software as part of the system allows for swift application development. **Oncilla Machine Vision Computers** include a license for ActiveSDK, Active Silicon's Software Development Kit. This provides comprehensive example applications and optimized libraries. Coupled with the installed ActiveCapture tool for camera and frame grabber control, they allow rapid system development and integration (separate datasheets are available that describe [ActiveCapture](#) and [ActiveSDK](#) in detail).



Drivers for third party applications are also available such as Cognex VisionPro, HALCON, Common Vision Blox, StreamPix, LabVIEW etc.

The heart of the **Oncilla Machine Vision Computer** is the FireBird Quad CXP-12 Frame Grabber. Each CoaXPress connection supports up to 12.5 Gbps data rates, along with device power up to 13W and device control at up to 42 Mbps – all on a single coax cable. For faster devices, connections can be concatenated to provide multiples of the single coax bandwidth. Very long cable lengths are supported – up to 35m at 12.5 Gbps and 100m at 3.125 Gbps using Belden 1694A cable – or even longer lengths using thicker cables.

Active Silicon was one of the primary authors of the international CoaXPress standard, which is hosted by the JIIA (Japan Industrial Imaging Association). All our CoaXPress products are certified compliant to the specification through the JIIA CoaXPress Product Certification Program.

The **Oncilla system** with integrated FireBird frame grabber is designed for ultimate performance using Active Silicon's proprietary DMA Engine technology, "ActiveDMA". This technical innovation applies RISC based processor techniques and guarantees high speed and low latency image data transfers and zero CPU intervention. Finally, full GenICam support is provided with the frame grabber drivers and this includes a GenTL Producer for data streaming as well as register accesses. Additional to functions that control the hardware, the libraries include general purpose functions for the manipulation and display of images.

## INDUSTRIAL PC SPECIFICATION

---

*Oncilla Industrial PC System:* Processor:

- 12th Generation Intel® Alder Lake-S Series CPU: Intel® Core™ i7-12700E (12 Cores / 35W TDP).

Chipset:

- Intel R680E.
- 

*Graphics:*

Display Ports:

- 1x VGA connector (1920 x 1080 @ 60Hz).
- 2x DisplayPort connector (4096 x 2304 @ 60Hz). Verified maximum DP resolution (3840 x 2160 @ 60Hz).
- 1x HDMI connector (4096 x 2160 @ 30Hz). Verified maximum DP resolution (3840 x 2160 @ 30Hz).
- Supports quad independent displays.

Graphics Chipset:

- Integrated Intel® UHD Graphics 770.
- 

*I/O:*

LAN:

- 2x GbE LAN (RJ45) (GbE1: Intel® I219 / GbE2: Intel® I210).

COM:

- 2x RS-232/422/485 with Auto Flow Control (Supports 5V/12V) (DB9).

USB:

- 2x USB 3.2 Gen2x1 (10 Gbps) (Type A).
- 4x USB 3.2 Gen1x1 (5 Gbps) (Type A).
- 2x USB 2.0 (480 Mbps) (Type A).

PS/2:

- 1x PS/2 (6 Pin Mini-DIN Female Connector).
- 

*Storage:*

Memory:

- 16GB 4800MHz DDR 5 SDRAM.

SSD Storage:

- 256GB M.2 SSD.

Storage Expansion (not fitted in standard build):

- 1x 2.5" Internal SATA HDD/SSD Bay (SATA 3.0).
  - 3x mSATA Socket (SATA 3.0 shared by Mini-PCIe socket).
-



---

<i>Storage (cont'd)</i>	RAID Support: <ul style="list-style-type: none"><li>• RAID 0/1/5/10.</li></ul>
-------------------------	--

---

<i>Expansion:</i>	PCIe expansion slots: <ul style="list-style-type: none"><li>• Slot 1: x16 – FireBird 4xCXP-12 with PEG connector for PoCXP support.</li><li>• Slot 2: x1 – Free for user expansion.</li></ul> Mini PCIe slots: <ul style="list-style-type: none"><li>• 3x Full-size Mini-PCIe socket.</li></ul> CMI (Combined Multiple I/O) Interface: <ul style="list-style-type: none"><li>• 2x High Speed CMI Interface.</li><li>• 2x Low Speed CMI Interface.</li></ul> CFM (Control Function Module) Interface: <ul style="list-style-type: none"><li>• 1x CFM IGN Interface for optional CFM-IGN Module.</li></ul>
-------------------	--

---

## FIREBIRD FRAME GRABBER SPECIFICATION

---

<i>CoaXPRESS Interface:</i>	Four 75 Ohm HD-BNC connectors (also known as Micro-BNC) each operate at all CXP speeds up to 12.5 Gbps. Up to 17W is available to power cameras on each HD-BNC via Power over CoaXPRESS (PoCXP), with 13W available at the camera according to the CoaXPRESS specification.  FireBird Quad CXP-12 supports one camera using all four connections, two cameras each using two connections, or up to four cameras each using one connection.  LEDs on the end bracket show the link status according to the CoaXPRESS specification.
-----------------------------	--

---

<i>Buffer Memory:</i>	Up to 4 Gbytes of DDR4 memory is fitted to the frame grabber for buffering between the card and PC memory.
-----------------------	--

---

<i>PCI Express:</i>	PCI Express 3.0 (Gen3) x8 interface to Specification Revision 3.1, with a max payload size of 512 bytes.  FireBird Quad CXP-12 supports both Short (32-bit) and Long (64-bit) Address packets. It also generates Posted Writes for image data, thus achieving transfer rates up to 6.8 Gbytes/sec, subject to host workload.
---------------------	--

---

<i>I/O:</i>	The following I/O lines are provided for triggers, optical shaft encoders, exposure control and general I/O: <ul style="list-style-type: none"><li>• 4x opto-isolated inputs.</li><li>• 4x opto-isolated outputs.</li><li>• 4x TTL inputs, 5V tolerant.</li><li>• 4x TTL I/O, 5V logic.</li><li>• 4x RS-422 inputs.</li><li>• 4x RS-422 outputs.</li></ul> All these I/O signals are provided on a 50-way header on the FireBird board. A 15-way D-Type connector is located on the end bracket and allows access to a subset of the above I/O: <ul style="list-style-type: none"><li>• 2x opto-isolated inputs.</li><li>• 3x TTL I/O, 5V logic.</li><li>• 2x RS-422 inputs.</li><li>• 1x RS-422 output.</li></ul>
-------------	---

---

<i>Software:</i>	ActiveCapture – image acquisition and control software. ActiveSDK – C/C++ libraries and example designs.
------------------	---

---



## CONFORMANCE

<i>CoaXPress:</i>		FireBird Quad CXP-12 conforms to v2.1 of the CoaXPress specification.
<i>Industrial PC Approvals:</i>	EMC	CE, UKCA, FCC, ICES-003 Class A. EN 50155 (EN 50121-3-2 Only).
	EMI	CISPR 32 Conducted & Radiated: Class A. EN/BS EN 50121-3-2 Conducted & Radiated: Class A. EN/BS EN IEC 61000-3-2 Harmonic current emissions: Class A. EN/BS EN61000-3-3 Voltage fluctuations & flicker. FCC 47 CFR Part 15B, ICES-003 Conducted & Radiated: Class A.
	EMS	EN/IEC 61000-4-2 ESD: Contact: 6 kV; Air: 8 kV. EN/IEC 61000-4-3 RS: 80 MHz to 1000 MHz: 20 V/m. EN/IEC 61000-4-4 EFT: AC Power: 2 kV; Signal: 2 kV. EN/IEC 61000-4-5 Surges: AC Power: 2 kV. EN/IEC 61000-4-6 CS: 10V. EN/IEC 61000-4-8 PFMF: 50 Hz, 1A/m. EN/IEC 61000-4-11 Voltage Dips & Voltage Interruptions: 0.5 cycles at 50Hz.
	Safety	UL, cUL, CB, IEC, EN 62368-1.
	Shock and Vibration	MIL-STD-810G.
<i>FireBird Approvals:</i>	EU	CE mark for compliance with EMC EN 55022:2010 (class A) and EN 55024:2010 in accordance with EU directive 2014/30/EU. RoHS compliance to RoHS3 directive 2015/863/EU.
	USA	EMC FCC Class A. The printed circuit board is manufactured by UL recognized manufacturers and has a flammability rating of 94V-0.
<i>Oncilla System Approvals:</i>		Full system EMC testing is currently on going, approvals data will be shown soon.

## PHYSICAL AND ENVIRONMENTAL DETAILS

<i>Dimensions: (W x D x H):</i>	227 x 261 x 128 mm.
<i>Approximate weight:</i>	5440g.
<i>Power Input:</i>	9-48VDC, 3-pin Terminal Block.
<i>Storage Temperature:</i>	-15°C to +85°C.
<i>Operating Temperature:</i>	0°C to +60°C (ambient environment). (According to IEC60068-2-1, IEC60068-2-2, IEC60068-2-14.)
<i>Relative Humidity:</i>	10% to 90% non-condensing (operating and storage).



## ORDERING INFORMATION

<b>PART NUMBER</b>	<b>DESCRIPTION</b>
<b>AS-ONC-1402-24W-4XCXP-A</b>	<b>Oncilla Machine Vision Computer – CoaXPRESS</b> Standard 2024 1402 chassis, PCIe riser with 1 x16 Slot (inc. PEG connector) + 1 x1 slot, 1x AS-FBD-4XCXP12-3PE8, Microsoft Windows 11, ActiveCapture, ActiveSDK.
<b>AS-ONC-220W-PSU</b>	<b>Oncilla 220W Mains Power Supply Unit</b> 110/240V AC Input, 24V DC Output Supply including IEC cables for EU, UK, USA.
<b>Other Oncilla Machine Vision Solutions</b>	
<b>AS-ONC-1402-24W-4XCOF-A</b>	<b>Oncilla Machine Vision Computer – CoaXPRESS over Fiber</b> Standard 2024 1402 chassis, PCIe riser with 2 x8 Slots, 1x AS-FBD-4XCOF12-3PE8, Microsoft Windows 11, ActiveCapture, ActiveSDK.
<b>AS-ONC-1402-24W-1XCLD-A</b>	<b>Oncilla Machine Vision Computer – Camera Link</b> Standard 2024 1402 chassis, PCIe riser with 2 x8 Slots, 1x AS-FBD-1XCLD-2PE4, Microsoft Windows 11, ActiveCapture, ActiveSDK.
<b>Cable Solutions</b>	
<b>AS-CBL-1MM-0010-xM</b>	HD-BNC (micro-BNC) to HD-BNC cable x meters in length for use with CoaXPRESS video sources. Made from Belden 4855R cable rated to CXP-12.  The standard stock length is 3m, 5m and 10m.  High-flex rating and much longer length cables also available – contact your distributor for details.
<b>AS-CBL-1BM-0010-xM</b>	As above, but HD-BNC to BNC. Standard stock length: 3m, 10m.
<b>AS-CBL-1DM-0001-xM</b>	As above, but HD-BNC to DIN1.0/2.3 and made from Belden 1855A cable rated to CXP-6 (DIN connectors are only supported in CXP up to CXP-6 speeds). Standard stock length: 3m, 10m.



## CONTACT DETAILS

**UK Office:**

Active Silicon Ltd  
1 Waterside Court, Waterside Drive,  
Langley, Berks, SL3 6EZ, UK.

Tel: +44 (0)1753 650600  
Email: [info@activesilicon.com](mailto:info@activesilicon.com)  
Website: [www.activesilicon.com](http://www.activesilicon.com)

**US Office:**

Active Silicon, Inc.  
479 Jumpers Hole Road, Suite 301,  
Severna Park, MD 21146, USA.

Tel: +1 410-696-7642  
Email: [info@activesilicon.com](mailto:info@activesilicon.com)  
Website: [www.activesilicon.com](http://www.activesilicon.com)

20-Nov-2024